



Transtank[®]
INTERNATIONAL

Operator's Product HandBook

LinkOn[™]

3PL Tractor Boom Sprayer



“HELPING TO DEVELOP AND PROTECT THE LAND”

Contents

Safety	4
General Safety Instructions	5
General Information	6
Specifications	6
Description	6
Machine Limitations	9
Driving Stability	9
Spray Boom Calibration	9
Calibration Procedure	10
LinkOn Operating Instructions	13
Before First Use	13
Filling the LinkOn Tank	16
Operating Instructions	16
Clean-up and Decontamination	21
Cleaning Procedure	21
Cleaning Procedure using Flush Tank	22
Maintenance	23
Periodic Checks	23
Maintenance Schedule	24
Maintenance Tasks	25
Trouble Shooting	26
Pump	26
Risk Assessment	27
Warranty	28
Warranty Policy	28
What this Warranty Does Not Cover?	28
How to Obtain Service Under this Warranty?	28
Warranty Limitations	28

Disclaimer

All information, illustrations, and specifications contained in this manual are based on the latest product information available at the time of this publication's printing. TransTank International (TTi) reserves the right to alter and substitute specifications and methods at any time, in line with our commitment to continuous improvement.

No patent liability is assumed with respect to the use of information contained within this manual. While every precaution has been taken in the preparation of this manual, TTi assumes no responsibility for errors or omissions.

Thank you for purchasing a TTi LinkOn[™] 3-Point Linkage Professional Sprayer (LinkOn), which will provide many years of reliable service when operated and maintained in accordance with this manual.

TTi manufacture a range of LinkOn units, from 300 to 1,000 litre tanks. The LinkOn is supplied complete with a Bertolini pump powered directly from the tractor's power take-off (PTO) and incorporates a 10 litre handwash tank with tap. The LinkOn is available with a range of options, including a flush tank, spray boom options, 30m hose reel, foam marker kit, GPS system and remote electrical control switch. This manual describes the operation, driving stability and maintenance procedures applicable to all units, noting additional requirements to options where necessary.

All TTi LinkOn tanks are rotationally moulded from quality polyethylene, purpose designed and manufactured to high standards. The LinkOn is specifically designed to mount directly onto your tractor and used for everything from herbicide to pesticide spraying.

The LinkOn unit is supplied complete, tested and ready to hitch to your tractor. TTi warrants that the LinkOn has been designed and built for its intended purpose as a pesticide/herbicide spray unit.

The owner is responsible to ensure that the equipment is operated in accordance with this manual, with Australian WorkSafe requirements, applicable road rules and local council regulations. TTi is not liable for any loss, injury or death resulting from the failure to observe all safe working regulations as required by law.

Included with your LinkOn unit are the following documents:

- Operator's Handbook (this manual, which includes the Warranty Registration Card)
- Bertolini pump data sheet (includes link to download pump manual). TTi recommends that you download this manual.
- Tank Quality Check Form. This is your verification that the unit has been quality checked, and verifies the serial number affixed to the unit.

Safety

This manual is intended for use by personnel experienced in the use of this and similar equipment. Read and understand this manual before attempting to operate or perform routine maintenance on this equipment. Your safety is of prime priority.



A WARNING highlights an essential operating or maintenance procedure, practice, condition or statement, which, if not strictly observed, could result in injury or death of personnel, or long-term health hazards.



A CAUTION highlights an essential operating or maintenance procedure, practice, condition or statement, which, if not observed, could result in damage or destruction of equipment.



A NOTE highlights or clarifies an essential systems description, operating or maintenance procedure, condition or statement.

General Safety Instructions

1. This unit is designed and manufactured solely for the purpose of carrying and spraying herbicides and pesticides. Under no circumstances should it be used for any other purpose. It must never be used for transporting fuel.
2. Only authorised and trained personnel are to operate this equipment. Operators must have read and fully understood this manual before operating the LinkOn unit.
3. Do not operate the LinkOn anywhere near bystanders, livestock, watercourses or any non-targeted vegetation that may be in danger from spray drift contamination.
4. Wind direction and speed must be taken into account, as windy conditions may endanger the operator or damage to adjacent non-target vegetation. Avoid spraying on hot and sunny days or when wind speed exceeds 6.5km/h.
5. Do not operate this equipment while under the influence of alcohol or any drugs that could impair your capabilities in any way.
6. PPE appropriate to the chemicals being used must be worn at all times when operating the LinkOn. As a minimum, the PPE should include coveralls, gloves and boots. A face shield and PVC apron are recommended depending on the task. It is recommended that the following documents should be read and understood by the operator:
 - Australian Standard for Chemical protective clothing AS3765
 - Australian Standard for Respiratory protection devices AS1715
7. Ensure the capacity of the tractor is suitable for the loaded mass of the LinkOn. Refer to the vehicle's operator manual for safe working loads, correct securing points and relevant safety instructions. Do not exceed the carrying and braking capacity as specified by the vehicle manufacturer. As a guide, one litre of water weights one kilogram (kg), therefore a full 300 litre LinkOn will weigh in excess of 350kg.
8. The unit must be securely attached to the tractor's 3-point linkage. Ensure the linkages are secured correctly before operation.
9. Care should be taken at all times, particularly when operating on rough or steep terrain. Drivers should be aware of fluid surge affecting the vehicle's centre of gravity.
10. The LinkOn must never be left unattended while being filled with fluids.
11. Do not operate the pump when there is no fluid in the tank.
12. Do not disconnect any hoses, nozzles or filters while the equipment is operating. Disconnecting any components while under pressure may result in uncontrolled fluid discharge which may be hazardous.
13. Ensure any electrical connections are properly configured, to prevent damage such as shorting or reverse polarity.
14. At completion of operation, turn the pump off and relieve any residual pressure by squeezing the optionally fitted spray gun trigger or opening a spray boom valve.
15. At completion of the operation, decontaminate the LinkOn tank and spray lines. Drain any residue chemicals and store in a sealed container. Dispose of any unwanted chemicals and tank rinse residue in accordance with current environmental and workplace health and safety regulations.
16. The LinkOn has safety labels affixed to various locations on the unit. These labels should be kept clean and legible, and replaced if damaged.
17. Any unauthorised modifications to this equipment may affect its function and create a serious safety risk. Any unauthorised modifications will void any warranty on the unit.

General Information

Specifications

Tank	UV stabilised, chemical resistant polyethylene tank complete – 300, 400, 600, 800 and 1,000 litre capacities, incorporating 10L handwash tank with tap
Frame	Heavy duty, fully welded, hot dipped galvanised steel frame with forklift pockets and adjustable boom height settings
Standard Equipment	<p>Bertolini PTO-driven pump – 22L/min to 75L/min, depending on LinkOn unit</p> <p>Pressure regulator and gauge</p> <p>PTO shaft</p> <p>Tank level gauge</p>
Options	<p>Compact™ Break-away steel booms, with 4m, 6m or 8m spray swath</p> <p>Pinnacle™ Self-leveling steel booms, with 8m, 10m and 12m spray swath</p> <p>30m hose on hose reel with spray gun</p> <p>Double-sided foam marker kit with solenoid control (for 6m and above boom options)</p> <p>TeeJet Matrix 430 GPS Guidance System</p> <p>Remote control solenoid operated ON-OFF switch unit</p>

Description

TTi LinkOn Professional Sprayer is designed to carry and distribute herbicides or pesticides using an integral pump and various fluid dispensing systems. The LinkOn variants are configured as follows:

- LinkOn – 300 or 400 litre tank unit with Bertolini 22L/min pump, available with the following options:
 - 30m hose on hose reel with spray gun
 - 4m or 6m Compact Break-away Spray Boom
- LinkOn – 600, 800 or 1,000 litre tank unit with Bertolini 75L/min pump, available with the following options:
 - 30m hose on hose reel with spray gun
 - 4m, 6m or 8m Compact Spray Break-away Boom
 - 8m, 10m or 12m Pinnacle Self-leveling Boom
 - Double-sided foam marker kit with solenoid control (for 6m and above boom options)
 - TeeJet Matrix 430 GPS Guidance System
 - Remote main electrical control ON-OFF switch unit

The LinkOn has the following features, refer to Figure 1.




Figure 1 – Component Identification – LinkOn with hose reel option

Pump

The 300 and 400 litre tank LinkOn units are fitted with a Bertolini 22L/min pump. The 600, 800 and 1,000 litre tank LinkOn units are fitted with a Bertolini 22L/min pump. All LinkOn units have their pumps driven directly off the tractor's PTO.

If the spray boom or optional spray gun is not in operation when the pump is running, the fluid bypasses back into the tank.

4m, 6m and 8m Compact Spray Break-away Booms

The 4m and 6m spray swath Compact Spray Break-away Boom can be fitted to the 300 and 400 litre tank LinkOn units. The 8m boom is recommended for the 600 litre and above tank capacities. The galvanised boom has steel plate protected non-drip nozzles fitted with TeeJet AIXR Air Induction spray tips. The boom incorporates a break-away feature to prevent damage if the unit hits an obstacle, and easily folds for transportation and storage.

8m, 10m and 12m Pinnacle Self-leveling Booms

These Pinnacle booms can be fitted to the 600, 800 and 1,000 litre tank LinkOn units. The galvanised boom has steel plate protected non-drip nozzles fitted with TeeJet AIXR Air Induction spray tips. The boom incorporates a break-away feature to prevent damage if the unit hits an obstacle, and easily folds for transportation and storage. The boom structure incorporates a self-leveling mechanism to take into account uneven terrain. From the driver's seat, the operator can start and stop spray operations using the optional electrically operated solenoid valve on the 3-way regulator.

Foam Marker Kit

An optional Foam Marker Kit is available for the LinkOn when fitted with boom options of 6m and above. The kit includes a 20L container with a spray nozzle mounted on each end of the boom. With the container filled with a rich soapy water solution, the electrically actuated solenoid valve operates at factory-set intervals to discharge a short burst of foam onto the ground. This provides a visual indication of the spray swath run, enabling accurate coverage for the next, adjacent pass.

Power for the solenoid valve is provided by the tractor's electrical system via the supplied cable and controller.

30m Hose Reel and Spray Gun

The LinkOn has an optional manually operated hose reel containing 30m of 10mm diameter hose connected to a trigger actuated PowerJet spray gun with adjustable brass nozzle. The hose is pulled out manually from the reel and retracted using the handle on the side. The spray gun is stowed vertically in a holder incorporated in the galvanised steel frame.

The nozzle adjusts from jet through to mist sprays by rotating the nozzle head. When the trigger is squeezed, the fluid is discharged; when the trigger is released, the fluid bypasses back into the tank.

Pressure Regulator

A pressure regulator and pressure gauge are mounted to the galvanised steel frame to control line pressure and prevent pump cavitation. The regulator is adjustable depending on the operation requirements – for boom spraying, the regulator is to be set to approximately 3 bar; with spot spraying via the optional hose the regulator is set to approximately 5 bar.

Manually Operated Valves

A manually operated 3-way valve is fitted to the pressure regulator manifold of the 300 litre LinkOn unit, to provide fluid to the spray boom feed line or optional hose reel. On the 400 litre and above LinkOn units, the manually operated valves are incorporated into the pressure regulator manifold, enabling individual adjustment of boom spray operation and the optional hose reel.

Solenoid Operated Valve

An optional electrically operated solenoid valve is available for 600 litre and above LinkOn units. The solenoid valve is mounted on the pressure regulator manifold and turns the entire manifold either ON or OFF via the remote electrical control switch.

Suction Filter

A filter is installed on the suction line below the tank and protected by a guard incorporated into the steel frame. The filter has a removeable filter element for easy cleaning.

Frame

The LinkOn frames are fabricated all steel, fully welded and then hot dip galvanised for corrosion resistance. The base incorporates forklift pockets. The boom mount incorporates vertical slots, enabling the boom to be easily adjusted in height.

PTO Shaft

Each LinkOn is provided with a universal PTO shaft, which is adjustable in length to suit the tractor PTO location in relation to the 3-point linkage.

Tank

All TTI tanks are constructed from UV stabilised, chemical resistant, virgin material polyethylene. The tank is fully drainable and has an internal basket strainer under the filling cap. Incorporated into the LinkOn tank is a 10-litre handwashing water tank and tap.

Tank Level Indicator

A level sight tube is fitted to the rear of the tank and provides an accurate level indication of fluid within the tank. The sight tube can be seen from the tractor's driver's seat, allowing the operator to monitor the tank level.

Flush Tank

A flush tank can be optionally mounted onto the LinkOn tank. A 3-way control valve draws water from the flush tank through the lines and optional hose reel. The main tank can be then flushed with clean water by removing the suction line from the sum

Machine Limitations

The LinkOn units are subject to operating limitations. It is the operator's responsibility to ensure that this equipment is being operated safely and within these limitations.

Driving Stability

The LinkOn unit is heavy when filled with fluid. To maintain stability while operating this unit:

- Ensure the tractor tyres are inflated to their correct pressure at all times. Underinflated tyres can cause excessive lateral motion of the tyre, which may cause a rollover.
- Allow extra room for braking and turning when the tank is full.
- Ensure any side gradient (slope) is accounted for, especially when the LinkOn tank is full, as the tractor may have a higher centre of gravity.

Spray Boom Calibration

Accurate calibration is an essential element of any spraying function as it ensures that the chemical is applied at the rate specified on the product label. Application in excess of the recommended rate may be dangerous, can damage crops and is uneconomical.

Calibration must be carried out:

- When spraying for the first time with new spray equipment
- At the beginning of each season
- After changes of nozzle tips, spraying pressure or vehicle speed
- After every 100 hectares of spraying

PPE appropriate to the chemicals being used must be worn at all times when calibrating the LinkOn. As a minimum, the PPE should include coveralls, gloves and boots. A face shield and PVC apron are recommended.

Calibration Procedure

Check the label on the chemical container for the application rate and recommended spray nozzle type, refer to Figure 2, which shows the TeeJet AIXR nozzle application chart. To apply a specific rate of chemical to the target surface, work out the:

- total sprayer output,
- travel speed, and
- the swath width.

Using these parameters, the application rate is calculated as follows.

Measure Total sprayer output [L/min]

Set the pressure at the correct level for spraying determined by the type of nozzles. All nozzles used for spraying should be left on. For initial trials, set the pressure regulator at approximately 2 bar and adjust as needed.

- Fill the spray tank with clean water, refer to Filling the LinkOn Tank procedure below. Run the sprayer at the correct pressure with all nozzles operating.
- Place a measuring jug under first nozzle for one minute, then measure how much water is in the jug.
- Repeat for all nozzles. Nozzle output should not vary by more than 10%. If it does, the nozzle could be worn or damaged and should be replaced.
- Add all the jug measurements to find the total sprayer output in litres per minute.

Measure the travel speed [km/h]

The normal speed for spraying with small boom sprayers is 4–10 km/h. The slower the travel, the higher the application rate. Adjust travel speed to suit ground conditions.

- Measure how many seconds it takes to travel 100 metres with the sprayer attached and half full.
- Calculate your travel speed by inserting the time in seconds into the following formula: *Travel speed (km/h) = distance travelled in metres (say 100m) x3.6 / Time taken (in seconds)*

Calculate spray application rate [L/Ha]

The normal speed for spraying with small boom sprayers is 4–10 km/h. The slower the travel, the higher the application rate. Adjust travel speed to suit ground conditions.

- Measure how many seconds it takes to travel 100 metres with the sprayer attached and half full.
- Calculate your travel speed by inserting the time in seconds into the following formula: *Travel speed (km/h) = distance travelled in metres (say 100m) x3.6 / Time taken (in seconds)*

Calculate spray application rate [L/Ha]

First, measure the swath width in metres. For general broadcast spraying, the swath width is equal to the number of nozzles multiplied by the nozzle spacing. For band spraying, the swath width is equal to the total of all the band widths. Calculate the application rate using the following formula:

$$\text{Application rate (L/ha)} = (600 \times \text{total sprayer output (L/min)}) / (\text{swath width (m)} \times \text{travel speed (km/h)})$$

Example: If total sprayer output is 5 L/min, speed is 8 km/h, and swath width is 4m, the application rate = $(600 \times 5 = 62.5 \text{ L/ha}) / (4 \times 8)$

If the application rate is less than specified, increase the pressure and repeat calibration to achieve the correct rate. Once the required rate is achieved, note the following parameters for future reference when using this particular chemical:

- Nozzle Fitted
- Type (Drop Size)
- Application Rate
- Spray Pressure
- Forward Speed.

Nozzle Icon	Pressure (bar)	Drop Size	LERAP Ratings	Capacity One Nozzle in L/min	l/ha								CAP PART NUMBER			
					50 cm											
					5 km/h	6 km/h	7 km/h	8 km/h	10 km/h	12 km/h	16 km/h	18 km/h	20 km/h			
AIXR110015 (100)	1.0	XC	-	0.34	81.6	68.0	58.3	51.0	40.8	34.0	25.5	22.7	20.4	114411-CELR		
	2.0	C	-	0.48	115	96.0	82.3	72.0	57.6	48.0	36.0	32.0	28.8			
	3.0	C	-	0.59	142	118	101	88.5	70.8	59.0	44.3	39.3	35.4			
	4.0	M	-	0.68	163	136	117	102	81.6	68.0	51.0	45.3	40.8			
	5.0	M	-	0.76	182	152	130	114	91.2	76.0	57.0	50.7	45.6			
6.0	M	-	0.83	199	166	142	125	99.6	83.0	62.3	55.3	49.8				
AIXR11002 (50)	1.0	XC	-	0.46	110	92.0	78.9	69.0	55.2	46.0	34.5	30.7	27.6		114412-CELR	
	2.0	VC	-	0.65	156	130	111	97.5	78.0	65.0	48.8	43.3	39.0			
	3.0	C	-	0.79	190	158	135	119	94.8	79.0	59.3	52.7	47.4			
	4.0	M	-	0.91	218	182	156	137	109	91.0	68.3	60.7	54.6			
	5.0	M	-	1.02	245	204	175	153	122	102	76.5	68.0	61.2			
6.0	M	-	1.12	269	224	192	168	134	112	84.0	74.7	67.2				
AIXR110025 (50)	1.0	XC	**	0.57	137	114	97.7	85.5	68.4	57.0	42.8	38.0	34.2			114413-CELR
	2.0	VC	**	0.81	194	162	139	122	97.2	81.0	60.8	54.0	48.6			
	3.0	VC	**	0.99	238	198	170	149	119	99.0	74.3	66.0	59.4			
	4.0	C	**	1.14	274	228	195	171	137	114	85.5	76.0	68.4			
	5.0	C	**	1.28	307	256	219	192	154	128	96.0	85.3	76.8			
6.0	M	-	1.40	336	280	240	210	168	140	105	93.3	84.0				
AIXR11003 (50)	1.0	XC	**	0.68	163	136	117	102	81.6	68.0	51.0	45.3	40.8	114414-CELR		
	2.0	VC	**	0.96	230	192	165	144	115	96.0	72.0	64.0	57.6			
	3.0	VC	**	1.18	283	236	202	177	142	118	88.5	78.7	70.8			
	4.0	C	**	1.36	326	272	233	204	163	136	102	90.7	81.6			
	5.0	C	**	1.52	365	304	261	228	182	152	114	101	91.2			
6.0	M	-	1.67	401	334	286	251	200	167	125	111	100				
AIXR11004 (50)	1.0	UC	***	0.91	218	182	156	137	109	91.0	68.3	60.7	54.6		114415-CELR	
	2.0	XC	**	1.29	310	258	221	194	155	129	96.8	86.0	77.4			
	3.0	VC	**	1.58	379	316	271	237	190	158	119	105	94.8			
	4.0	VC	**	1.82	437	364	312	273	218	182	137	121	109			
	5.0	C	**	2.04	490	408	350	306	245	204	153	136	122			
6.0	C	-	2.23	535	446	382	335	268	223	167	149	134				
AIXR11005 (50)	1.0	UC	***	1.14	274	228	195	171	137	114	85.5	76.0	68.4			114416-CELR
	2.0	XC	***	1.61	386	322	276	242	193	161	121	107	96.6			
	3.0	VC	**	1.97	473	394	338	296	236	197	148	131	118			
	4.0	VC	**	2.27	545	454	389	341	272	227	170	151	136			
	5.0	C	**	2.54	610	508	435	381	305	254	191	169	152			
6.0	C	-	2.79	670	558	478	419	335	279	209	186	167				
AIXR11006 (50)	1.0	UC	***	1.37	329	274	235	206	164	137	103	91.3	82.2	114417-CELR		
	2.0	XC	***	1.94	466	388	333	291	233	194	146	129	116			
	3.0	VC	***	2.37	569	474	406	356	284	237	178	158	142			
	4.0	VC	**	2.74	658	548	470	411	329	274	206	183	164			
	5.0	C	**	3.06	734	612	525	459	367	306	230	204	184			
6.0	C	-	3.35	804	670	574	503	402	335	251	223	201				
AIXR11008 (50)	1.0	UC	-	1.82	437	364	312	273	218	182	137	121	109		114418-CELR	
	2.0	XC	-	2.58	619	516	442	387	310	258	194	172	155			
	3.0	VC	-	3.16	758	632	542	474	379	316	237	211	190			
	4.0	VC	-	3.65	876	730	626	548	438	365	274	243	219			
	5.0	VC	-	4.08	979	816	699	612	490	408	306	272	245			
6.0	C	-	4.47	1073	894	766	671	536	447	335	298	268				
AIXR11010	1.0	UC	-	2.28	547	456	391	342	274	228	171	152	137			114419-CELR
	2.0	UC	-	3.23	775	646	554	485	388	323	242	215	194			
	3.0	XC	-	3.95	948	790	677	593	474	395	296	263	237			
	4.0	VC	-	4.56	1094	912	782	684	547	456	342	304	274			
	5.0	VC	-	5.10	1224	1020	874	765	612	510	383	340	306			
6.0	VC	-	5.59	1342	1118	958	839	671	559	419	373	335				

NOTE: Always double check your application rates. Tabulations are based on spraying water at 21°C.

DROPLET SIZE CATEGORIES

XF	VF	F	M	C	VC	XC	UC
EXTREMELY FINE	VERY FINE	FINE	MEDIUM	COARSE	VERY COARSE	EXTREMELY COARSE	ULTRA COARSE

Droplet size may vary with nozzle capacity, spray angle and spray pressure.

Figure 2 – AIXR Application Chart

LinkOn Operating Instructions

Before first use

Your LinkOn 3-Point Linkage Professional Sprayer is delivered assembled and ready to be connected to the tractor. Before use, it needs to be set up using the following instructions:

Complete the warranty registration online at www.tti.com.au/warranty-registration, or use the Warranty Registration Card at the back of this handbook.

Store this handbook, along with the Tank Quality Check Form and pump unit's manual in a safe and easily accessible place for future reference.



WARNING: The operator must fully understand all aspects of this handbook. Do not operate the LinkOn unit if you are unfamiliar with its operation until you have read this handbook.

- Read and thoroughly understand this handbook, paying particular attention to all safety requirements, before using the LinkOn for the first time.
- Check that all fittings, valves, hoses and electrical leads are secure following transit, and are not damaged in any way.
- Inspect the tank for any damage or abrasions that may occur during transit.
- Remove the supplied PTO shaft from its transit/delivery location.



CAUTION: The LinkOn unit must be securely attached to the tractor. Failure to do so may result in the unit breaking away from the moving vehicle. Warranty is conditional on the unit being correctly coupled.

- Refer to the tractor's operating manual for the specific procedure to connect equipment to the tractor's 3-point linkage.
- Position the LinkOn unit on level, flat ground, ensuring it is stable. Use suitable chocks if required to ensure the unit is stable.
- Connect your LinkOn unit to the tractor's 3-point linkage in the following order:
 - Left link
 - Right link
 - Top link
- Ensure the three supplied pins are fitted correctly and each is secured with their locking clips.



CAUTION: The PTO shaft must be correctly installed between the LinkOn pump and the tractor's PTO output shaft. End thrust from an over-length shaft can destroy the tractor's internal PTO drive and/or the LinkOn pump.

- Raise or lower the LinkOn via the 3-point linkage to find the shortest gap between the ends of the tractor's PTO output and the LinkOn's splined shafts, refer to Figure 3.



Measure Groove to Groove Distance



Measure Shaft Length between Lock Buttons or Clamp Bolts



Cut Drive Tubes, Remove Burrs, Grease and Reassemble



Figure 3 – Fitting of PTO Shaft

- Prepare the PTO shaft as follows:
 - Accurately measure the groove-to-groove distance between the LinkOn shaft and the tractor's shaft. The required length of the shaft is this measurement minus 76mm to allow for disconnection from the tractor.



CAUTION: The shaft must have at a 50 percent overlap of the telescopic tubes.

- Remove the safety guard from the supplied PTO shaft. With the shaft in the closed (shortened) position, measure the length between the shaft lock button or clamp bolts. If the shaft is shorter than the measurement taken at step a, ensure that 50 percent of the telescopic tubes overlap.
- The shaft now needs to be cut to the required length, which is the length of the shaft MINUS the groove-to-groove measurement PLUS 76mm. Refer to the example shown in Figure 3.
- Cut both the inner and outer drive tubes. Remove burrs and grease the tubes.
- Insert the inner tube into the outer tube, to reassembly the PTO shaft.
- Connect the PTO shaft to the drive couple at the pump, then extend the PTO shaft and connect it to the PTO output shaft on the tractor. Ensure the PTO shaft is correctly coupled at each end.



CAUTION: Ensure any electrical connections are configured correctly to prevent shorting or reverse polarity. Warranty is conditional on the electrical systems being correctly connected.

- If optional, install the supplied electrical control ON-OFF switch unit at a suitable location near the driver's seat, then connect the cable to the tractor's power supply. Connect the other end to the solenoid switch at the regulator manifold.
- If the optional Foam Marker Kit is provided, install the electrical cable and connect it to the vehicle's power supply via the cable's plug, refer to Figure 4.



Figure 4 – Optional Foam Marker Kit Electrical Cables and Controller

- It is recommended that at first use, the LinkOn is filled with water for calibration purposes and for the operator to become familiar with the characteristics of the unit. Refer to the Calibration Procedure to set up the unit for first use; and each time there are different spray parameters required.

Filling the LinkOn Tank



CAUTION: Ensure the filling area is in an open, well-ventilated space if filling with chemicals. Follow the instructions provided with the chemicals or the applicable Safety Data Sheet.

Mixing and filling the LinkOn unit should be undertaken at a carefully chosen site, away from any risk of spillages draining into water courses or into environmentally sensitive areas. Children and animals must always be kept away from mixing and filling operations.

The LinkOn's tank is filled as follows:



NOTE: Ensure the manually operated isolating valve for the boom is CLOSED.

- Check that the boom's manual isolating valve is CLOSED, or the optional electrically controlled solenoid valve is OFF.
- Open the tank filler by twisting and lifting the cap.
- Withdraw the internal basket strainer and inspect it for any debris. Clean it if required and reinstall it into the top of the tank.
- Follow the chemical manufacturer's instructions and safety precautions carefully, taking note of the order in which the products are added to the tank.
- Measure the correct quantities of chemicals using clean measuring containers specifically for this purpose only, then add the chemicals to the tank.
- Rinse out the measuring containers and any empty containers and pour all rinsing liquid into the LinkOn tank.



CAUTION: Do not overfill the tank. This may result in chemical spillage.



CAUTION: The LinkOn must never be left unattended while being filled with fluid.

- Top up the tank with water to the required level, ensuring it is not overfilled.
- Thoroughly mix the contents by stirring with a suitable paddle or starting the PTO-driven pump to allow recirculation through the pump and back into the tank. Ensure the hose operation lever is in the closed (BYPASS) position.
- Upon completion of filling the LinkOn tank, replace the filler cap and twist to tighten.
- Wash off any spillage from outside the tank.
- Close the chemical supply containers and store appropriately. Any empty containers must be thoroughly rinsed and set aside for collection and disposal in compliance with environmental and work safety requirements.

Operating Instructions

The LinkOn is started and operated as follows:

- Confirm the tank contains the required chemical or water quantity.



NOTE: Ensure the pressure regulator is set to the minimum position.

- At the pump, check that the pressure regulator is set to the minimum position by turning the knob anti-clockwise, refer to Figure 5.




Figure 5 – Pressure Regulator

- Check that the operation lever is in the closed (BYPASS) position.
- Check that the spray boom isolating valve(s) adjacent to the tank is in the CLOSED position.

- Start the pump by engaging the tractor's PTO output shaft.
- With the pump running, turn the pressure regulator knob clockwise to the required pressure – approximately 3 bar for spray boom operation. If the optional hose reel is fitted, approximately 5 bar is required for hose operation. Refer to the calibration procedure described above for the actual required pressure setting.
- For spraying operations, refer to:
 - Hose Spray Operation
 - Spray Boom Operation

Hose Spray Operation

Set up and operation of the optional 30m hose reel spray system is conducted as follows:



WARNING: Suitable PPE must be worn by the operator when conducting manual hose spraying operations.



WARNING: Do not spray in windy conditions, where spray drift contamination may occur.

- Position the tractor with the LinkOn unit at a suitable point of the operations area.



NOTE: Ensure the manually operated isolating valve to the boom is CLOSED.

- For the LinkOn fitted with manually operated spray booms or the optional hose reel, ensure the isolating valve on the pressure regulator manifold is in the CLOSED position.
- Check that the pressure regulator is set to its minimum setting. Start up the pump by engaging the tractor's PTO output. The fluid will now be circulating through the system and returning to the tank via the bypass circuit.
- Set the pressure regulator to approximately 5 bar – this can be fine-tuned as required.



CAUTION: Ensure not to over-run the hose when pulling it out from the reel, as this may damage the hose or the fittings.

- Pull the hose from the LinkOn's optional hose reel to unwind it.
- Turn the operation lever from BYPASS to ON, which will now pressurise the hose.

- Aim the hose's spray gun in the required direction and squeeze the trigger. Adjust the spray pattern by rotating the brass nozzle tip or gun lever, depending of spray gun.
- Use a constant speed when spraying and release the trigger at the end of each swath or change of direction, to prevent overdosing. Work in parallel lines when spraying large areas, rather than swinging from side to side.
- At the end of the task, release the spray gun trigger and switch the operation lever to BYPASS. The fluid will automatically recirculate through the system and return to the tank via the bypass circuit until the pump is switched OFF.
- Disengage the tractor's PTO to turn the pump OFF. Aim the spray gun in the required direction and squeeze the trigger. This will release the residual pressure in the hose, which will result in a small amount of fluid discharging.
- With the hose pressure released, the hose is ready to stow back on the LinkOn hose reel, refer to Figure 6. Turn the handle at the side of the hose reel to wind it onto the spool, guiding the hose as necessary to ensure even distribution across the width of the reel. Allow enough slack in the hose to stow the spray gun in its holder on the side of the tank. The reel has a four-position locking device to prevent the hose unwinding during transit.




Figure 6 – Optional 30m Hose Reel

Spray Boom Operation



WARNING: Before commencing spraying, plan the work effectively to minimise potential contamination of adjacent areas.

Compact Boom Options

The Compact Boom options supplied do not require any adjustments prior to operation. The spraying operation is conducted as follows:



WARNING: Do not spray in windy conditions, where spray drift contamination may occur. Spray drift can be reduced by lower nozzle height, lower pressures or by fitting larger nozzles.

- Position the vehicle at the starting point of the operations area.
- At the boom, fold out each of the two boom extensions fully, ensuring they each “click” into place at the end of their travel.
- Start the pump by engaging the tractor’s PTO output. The fluid will recirculate through the system and return to the tank via the bypass circuit until the boom is set into operation.
- Set the pressure regulator to the correct setting as determined during calibration.
- At the pressure regulator manifold, turn the required valve(s) to ON, refer to Figure 5.
- Turn the operation lever from BYPASS to ON, or if supplied, from the driver’s seat, turn the optional control solenoid operated switch to ON. The fluid will now start to discharge from the boom spray nozzles.
- Commence driving the tractor at the speed determined during calibration to achieve the required spray outcome.
- If fitted, at the end of each swath or before turning around, switch the solenoid valve’s switch to OFF. When commencing the next swath, turn the switch back to ON.

Foam Marker Kit Operation

The Foam Marker Kit, available as an option for the LinkOn when fitted with 6m and above booms, is operated as follows:

- Connect the electrical cable to a suitable supply on the vehicle, refer to Figure 4.
- Fill the marker container with a rich soapy water solution such that it achieves a dense foam when ejected from the nozzle.
- From the driver’s seat, turn the solenoid valve’s switch from the central OFF position to either the left or right ON position, refer to Figure 7. The foam will now start to discharge in timed intervals from the selected nozzle at the end of the boom.
- Start the spraying operation as described above.
- Commence driving the tractor at the speed determined during calibration to achieve the required spray outcome. The foam will mark the edge of the current swath, enabling accurate alignment with the next swath, ensuring there is minimal overlap and no missed areas.



Figure 7 – Optional Foam Marker Controller

Clean-up and Decontamination

After use, the LinkOn unit must be thoroughly decontaminated inside and outside – including the pump, boom and optional hose and spray gun – to avoid damage to crops from any harmful pesticide spray residues. Decontamination also prevents sprayer corrosion and abrasion.

Cleaning the LinkOn should be undertaken at a carefully chosen site, away from any risk of spillages draining into watercourses or into environmentally sensitive areas. The following describes the normal cleaning procedure, followed by the cleaning procedure where the optional flush tank is fitted to the LinkOn unit.

Cleaning Procedure

The recommended decontamination procedure is as follows:



WARNING: Suitable PPE must be worn by the operator when cleaning and decontaminating the LinkOn unit. Follow the instructions provided with the chemicals or the applicable Safety Data Sheet.



WARNING: Ensure the cleaning area is in an open, well-ventilated space, and any flushing water is captured to prevent runoff into watercourses or into environmentally sensitive areas.

- After spraying operations are complete, drain any residual fluid by opening the suction filter housing adjacent to the bottom of the tank, refer to Figure 8. Capture and dispose or store any fluid in accordance with environmental and work safety requirements.



Figure 8 – Suction Filter

- Rinse out the tank with several changes of water, plus a recommended cleaning fluid. Where it can be reached internally, use a brush to scrub the inside of the tank.
- Operate the LinkOn unit with clean water, using both the spray boom and hose (as applicable), to ensure no chemical residue remains.
- Unscrew the suction filter cover and remove the filter screen and gasket. Soak the filter screen in clean water, brushing carefully with a nozzle brush. When re-assembling, ensure the gasket is in position.
- Ensure that the tank's basket strainer is free from chemical residue or debris.
- Nozzles, nozzle filters, nozzle caps and gaskets should be cleaned by soaking in water, brushing with a nozzle brush and allowed to dry. Do not blow through the nozzles or use wire or pins to clear any blockages.
- Dispose of all rinsing water in compliance with environmental and work safety requirements.

Cleaning Procedure using Flush Tank

Cleaning of the LinkOn unit fitted with the optional flush tank is conducted in a similar manner to the cleaning procedure described above, but noting the following:

- Ensure the flush tank contains water and the main LinkOn tank is empty.
- With the tractor's engine running, engage the PTO output to operate the LinkOn's pump.
- Adjacent to the optional hose reel, the 3-way valve handle should be pointing towards the tractor, refer to Figure 9. To draw water from the flush tank, move the valve handle to the upright position.



Figure 9 – Flush Tank Operation

At the pressure regulator manifold, individually turn each valve to ON for approximately 30 seconds or until each line is fully flushed.

- Once each line is fully flushed, direct the remaining flush tank water into the LinkOn's main tank by turning the operation lever to BYPASS.
- Drain the LinkOn's main tank by opening the suction filter housing adjacent to the bottom of the tank, refer to Figure 8.

If the LinkOn unit is to be stored for an extended period, thoroughly clean and decontaminate the unit as described above. Ensure it is allowed to dry, the tank and all lines empty and not pressurised then store it in a well ventilated area.



WARNING: The LinkOn sprayer may be unstable once disconnected from the tractor. Ensure it is suitably supported to prevent damage from falling over.

If the LinkOn is to be removed from the tractor, disconnect it in the opposite order to mounting, as described in the Before First Use section above. Ensure the unit is securely chocked once removed from the tractor.

Maintenance

Your LinkOn Professional Sprayer requires minimal maintenance but regular cleaning and checks will ensure safe and reliable service over its lifetime. Periodic checks and inspections will identify any potential issues, enabling timely rectification and minimising downtime.

Periodic Checks

The following checks and cleaning operations should be undertaken on a regular basis (at least annually). The frequency of these activities will depend on the nature of the operating environment and the operational hours of the LinkOn unit. Refer to the maintenance schedule tables below for details of maintenance intervals, noting that any petrol engine tasks are related to the LinkOn deluxe only.

- Clean the unit and inspect it for any signs of damage or wear. Replace any safety labels if they are damaged or illegible. Check all fittings are firmly secured, tighten if necessary.
- Unwind the optionally fitted hose fully to check that hose is in good order. Pressurise the line and check operation of spray gun nozzle. Rewind the hose onto the hose reel.
- Check the pump's oil level weekly, top up as required. Inspect of any signs of oil leaks around the pump.
- Check all electrical cables and fittings for any sign of damage.
- If the LinkOn is to be stored for an extended period, thoroughly clean and decontaminate the unit as described above. Ensure it is allowed to dry, the tank and all lines empty and not pressurised then store it in a well ventilated area.

Maintenance Schedule

The following tasks are to be conducted in accordance with each of the schedules. All scheduled tasks are to be undertaken concurrently. For example, at the three month maintenance interval, all task listed are to be undertaken, in addition to the daily, weekly and monthly tasks.



NOTE: Maintenance is important. Keep a record of all maintenance tasks conducted on the LinkOn unit.

TTi recommends photocopying these schedules in order to keep a detailed log of all maintenance tasks. A copy of these schedules will be required to support any warranty claim.

Daily tasks

The following tasks are to be undertaken daily, or prior to each use, of the LinkOn unit.

#	Task	Notes
1	Inspect the LinkOn unit for any signs of damage or wear	Clean, repair or replace
2	Check electrical plug connection	Test function of solenoid valve(s)

Weekly tasks

The following tasks are to be undertaken each week or 10 operating hours, whichever occurs first.

#	Task	Date	Signed
1	All Daily tasks		
2	Check pump oil level, top up as required (refer to Figure 10)		

Monthly tasks

The following tasks are to be undertaken each month or 20 operating hours, whichever occurs first.

#	Task	Date	Signed
1	All Daily and Weekly tasks		
2	Check optional hose and hose reel by unwinding fully		

Three Monthly tasks

The following tasks are to be undertaken every three months or 50 operating hours, whichever occurs first.

#	Task	Date	Signed
1	All Daily, Weekly and Monthly tasks		
2	Check all hoses, fasteners, nozzles and fittings		

Six Monthly tasks

The following tasks are to be undertaken every six months or 100 operating hours, whichever occurs first.

#	Task	Date	Signed
1	All Daily, Weekly, Monthly and 3-Monthly tasks		

Twelve Monthly tasks

The following tasks are to be undertaken every twelve months or 200 operating hours, whichever occurs first.

#	Task	Date	Signed
1	All Daily, Weekly, Monthly, 3-Monthly & 6-Monthly tasks		

Two-Yearly tasks

The following tasks are to be undertaken every 24 months or 500 operating hours, whichever occurs first.

#	Task	Date	Signed
1	All Daily, Weekly, Monthly, 3-Monthly, 6-Monthly and 12-Monthly tasks		
2	Change pump oil		
3	Replace pump check valves and diaphragms		

Maintenance Tasks

The following tasks must be undertaken on a periodic basis to ensure your LinkOn Professional Sprayer's ongoing reliability.



CAUTION: In dusty, dirty or smoky environments, cleaning, inspection and servicing of the unit on a regular basis is essential. The cleaning, inspection and servicing must be undertaken more frequently in harsh conditions to avoid damage or destruction of equipment.

The frequency of these activities will depend on the nature of the operating environment and the operational hours of the LinkOn but as a minimum, the following tasks should be undertaken annually.

PTO-driven Pump

- Unscrew the suction filter cover (refer to Figure 8) and remove the filter screen and gasket. Soak the filter screen in clean water, brushing carefully with a nozzle brush. When re-assembling, ensure the gasket is in position.
- Refer to the pump manual (downloaded via link on supplied data sheet), drain and replace the pump oil in accordance with the manufacturer's recommendations (refer to Figure 10).
- Replace the pump's check valves and diaphragms in accordance with the manufacturer's recommendations.




Figure 10 – Bertolini Pump

Trouble Shooting

If a fault develops with your LinkOn unit, the following trouble shooting tables provides guidance to identify and rectify the problem.

Pump

Problem	Possible Cause	Remedy
Pump will not prime	Air leak on suction line	Tighten or replace fittings
Pressure drops or fluctuates during operation	Suction line restriction	Remove restriction
	Pump sucks air	Tighten or replace fittings
No pressure	Broken regulator spring	Replace regulator spring

Risk Assessment

Task	Hazard	Risk	Control Measure/Mitigation
Check weather conditions	Manual handling; slips, trips or falls	Low	<ul style="list-style-type: none"> Wear PPE as per chemical requirements SDS – coveralls, gloves, safety footwear, glasses & respirator Follow safe manual handling techniques: don't lift on your own if >20kg, bend knees & keep back straight.
Mix chemicals (if applicable) and fill spray tank	As above, spray drift, chemical spillage, emission of vapours or flammability: weather, untrained visitors	Medium	<p>As above;</p> <ul style="list-style-type: none"> User trained in relevant chemical mixing & administration course, e.g, Chem Cert; Follow relevant Environmental Protection Authority requirements; Fire extinguisher nearby; Keep visitors away from job location unless wearing full PPE.
Check the Spray Unit and carry vehicle is safe before use, i.e. where applicable: - wheel nuts, tire pressure, bearings, tow hitch, etc. Use spray unit as per instructions in manual	As above; loss of load; heat & cold; noise; exceed load limit of vehicle; hose entanglement; exhaust fumes; terrain & slopes;	High	<p>As above;</p> <ul style="list-style-type: none"> wear clothes to suit heat & cold; Wear hearing protection if noise >85 dBA; Follow the manufacturer's safe operation instruction for the vehicle and the spray unit Don't overload - water weighs 1kg for every 1 litre Secure load to vehicle; Keep hose tidy; Put unit brakes on.
Clean up, maintenance & storage	As above	Low	<p>As above;</p> <ul style="list-style-type: none"> Continue to wear PPE for clean up; Store unit in a dry, well ventilated area.

Warranty

Warranty Policy

TTI will, at its option, repair or replace without charge any part covered by this warranty which is found to be defective in material and/or workmanship within one (1) year after date of sale to the original retail purchaser. If the product is used for rental purposes, this warranty is limited to ninety (90) days.

Upon request, the customer will make the defective part available for inspection and/or return the defective part to TTI, transportation charges prepaid. All parts and components are covered by this warranty except the following, which are warranted separately by their respective manufacturers:

- engines
- gearboxes
- pumps
- regulators.

TTi does not assume any warranty obligation, liability or modification for these items, which are covered exclusively by the stated warranty of the respective manufacturers.

What this Warranty Does Not Cover?

This warranty does not cover:

1. defects caused by depreciation or damage caused by incorrect mounting, normal wear, accidents, improper maintenance, improper use or abuse of the product, alterations or failure to follow the instructions and warnings provided.
2. Any charges for making service calls, clean up time and transport charges.
3. The use of non-genuine parts on equipment supplied by TTI. This will automatically negate any warranty.

How to Obtain Service Under this Warranty?

Warranty service can be arranged by contacting your dealer, or by contacting TTI directly on 1800 816 277.

Proof of warranty registration and date of purchase may be required to verify warranty coverage. Any defective parts returned to TTI must be accompanied by a Return Goods Note. This form can be obtained by contacting Product Support on 1800 816 277 or emailing ProductSupport@tti.com.au.

Warranty Limitations

Warranty limitations are as follows:

1. There is no other express warranty. Any warranty that may be implied from this purchase including merchantability and fitness for purpose is hereby limited to the duration of this warranty and to the extent permitted by law. Any and all implied warranties are excluded.
2. TTI will not be liable for any incidental, consequential or special damages and/or expenses in connection with the purchase or use of this equipment, to the extent permitted by law.
3. Only the warranty expressed in this limited warranty shall apply and no dealer, distributor or individual is authorised to amend, modify, or extend this warranty in any way. Accordingly, additional statements, whether oral or written, do not constitute warranties by TTI, and should not be relied upon.



TranTank[®]
INTERNATIONAL



Scan to view our PDF
Handbook online

1800 816 277

sales@tti.com.au

PO Box 137, Nathalia, VIC, 3638

Murray Valley Hwy, Nathalia, VIC 3638

Proudly Built By:

Signature

Date

Quality Checked By:

Signature

Date

www.tti.com.au