



TransTank[®]
International

The Safest Tanks in Motion

Product Specification

Diesel Refueling Trailers

DieselPatrol15™ 1200L

Dual Axle Trailer

SKU: DRQ1200LF060V1 (BRAKED)

SKU: DRX1200LF060V1 (UNBRAKED)



TTi's DieselPatrol15™ Refueling Trailers provide safe and hassle-free refueling for your plant and equipment. Our diesel refueling trailers feature a robust galvanized chassis, moulded poly diesel tanks, high flow pumps, and hose reels, ultimately delivering effortless refueling of equipment.

- » Exceptionally smooth towing with excellent weight distribution
- » Heavy-duty, fully-drainable, UV Stabilised poly tank with 15-year warranty
- » Fitted with LiquidLocker™ baffle system
- » Manufactured from specifically formulated diesel grade polyethylene that meets International Regulation ECE R34.01 requirements, and complies with AS1940-2004 and AS2809.2-2008
- » Built to high level ADR requirements, with heavy duty steel chassis featuring hot-dip galvanising for maximum protection for tough, long term durable performance
- » Fluid Italian 60L/min 12v Pump mounted in lockable toolbox
- » 65mm 2T-rated solid galvanised axles with 15" Landcruiser wheels
- » Recessed LED combination tail lights & license plate light
- » Large, 455mm lid opening with breather and filler cap
- » 50mm tow hitch
- » 2" Lockable filling point
- » Heavy duty chequer plate mudguards
- » Heavy duty jockey wheel
- » Greatly improved puncture resistance with our 6 ply radial tyres, which also helps heavy load capability
- » Hydraulic Override Braked (On-Road/Registrable) – On Farm (Unbraked) option available

SPECIFICATIONS

Tank Material	Polyethylene
Lid Diameter	455 mm
Safety Baffles	Fitted
Capacity (brim full)	1,200 Litres
Tare Weight (Braked)	570 kg
Tare Weight (UnBraked)	550 kg
Dimensions (L W H)	4000 x 1900 x 1410 mm
Tank Warranty	15-Year
Frame Warranty	5-Year
Pump Warranty	2-Year

www.tti.com.au

1800 816 277