



TransTank[®]
International

The Safest Tanks in Motion

Product Specification

Diesel Refueling Trailers

DieselPatrol15™ 2400L

Dual Axle Trailer

SKU: DRQD2400L060V1 (BRAKED)

SKU: DRXD2400L060V1 (UNBRAKED)



TTi's DieselPatrol15™ Refueling Trailers provide safe and hassle-free refueling for your plant and equipment. Our diesel refueling trailers feature a robust galvanized chassis, moulded poly diesel tanks, high flow pumps, and hose reels, ultimately delivering effortless refueling of equipment.

- » Exceptionally smooth towing with excellent weight distribution
- » Fully-drainable UV Stabilised poly tank with 15-year warranty
- » Manufactured from specifically formulated diesel grade polyethylene that meets International Regulation ECE R34.01 requirements, and complies with AS1940-2004 and AS2809.2-2008
- » Fitted with LiquidLocker™ baffle system
- » Large, 455mm lid opening
- » 2" lockable filling point
- » Fluid Italian 60L/min 12v Pump mounted in lockable toolbox
- » Built to high level ADR requirements, with heavy duty Hot-dipped galvanised chassis for maximum protection for tough, long term durable performance
- » Large 65mm 4T-rated solid galvanised axles with 15" famous Landcruiser wheels which provide high ground clearance and excellent maneuverability
- » Rocker-Roller suspension
- » 50mm Tow hitch
- » Heavy duty chequer plate mudguards
- » Greatly improved puncture resistance with our 6 ply radial tyres, which also helps heavy load capability
- » Heavy duty jockey wheel
- » Recessed LED combination tail lights & license plate light
- » Electric braked with break-away system (On-Road/Registrable) – On Farm (Unbraked) option available

SPECIFICATIONS

Tank Material	Polyethylene
Lid Diameter	455 mm
Safety Baffles	Fitted
Capacity (brim full)	2,400 Litres
Tare Weight (Braked)	870 kg
Tare Weight (UnBraked)	860 kg
Dimensions (L W H) - UnBraked	5000 x 2150 x 2790 mm
Dimensions (L W H) - Braked	5000 x 2150 x 2790 mm
Tank Warranty	15-Year
Frame Warranty	5-Year
Pump Warranty	2-Year

www.tti.com.au

1800 816 277