TransTark® International The Safest Tanks in Motion

Product Specification

LIQUID CARTAGE TANKS



SPECIFICATIONS

Tank Material	Polyethylene
Lid Diameter	255 mm
Capacity (brim full)	300 Litres
Tare Weight	17kg
(W) Full of Water	317kg
Tank (LWH)	1270 x 615 x 730mm
Tank w/ Frame (L WH)	1270 x 615 x 750mm
Tank Warranty	20-Years

<u>1800 816 277</u>

SumpTrans[™] 300L

Fully-Drainable Spray Tank

SKU: PTSS00300KSG - WITH FRAME SKU: PTSS00300SG - TANK ONLY

When full drainage is critical, the TTi's SumpTrans™ fully draining liquid cartage tanks are in demand. Designed and moulded to perform under any conditions, these pin mounted poly spray tanks have earnt their reputation as "The Safest Tanks in Motion".

- » Heavy-duty, chemical resistant polyethylene tank with 1.3 Specific Gravity (SG)
- » Fully draining sump for complete drainage and decontamination
- » 255mm lid with basket filter
- » 11/2" MBSP poly outlet fitted
- » Easy to read calibrated measurements
- » Steel support frame required to give sump clearance
- » Hot-dip galvanised steel frame for correct tank support & easy mounting
- » 20-Year Tank Warranty
- » Available Without Steel Frame Tank Only

www.tti.com.au