

DieselPatrol15™ 1000L

Single Axle Refueling Trailer

SKU: DRX1000LF060V1 (UNBRAKED)

SKU: DRQ1000LF060V1 (BRAKED)

TTi's DieselPatrol15™ Refueling Trailers provide safe and hassle-free refueling for your plant and equipment. Our diesel refueling trailers feature a robust galvanized chassis, moulded poly diesel tanks, high flow pumps, and hose reels, ultimately delivering effortless refueling of equipment.



- » Heavy-duty, fully-drainable, UV Stabilised poly tank with 25-year warranty
- » Built to high-level ADR requirements – manufactured from specially formulated diesel-grade polyethylene, complying with Australian Standards AS1940-2004 and AS2809.2-2008 for the safe transportation of flammable liquids and dangerous goods by road.
- » Strong heavy-duty Hot-dipped galvanised chassis with 50mm tow hitch
- » 60L/min 12v Piusi pump mounted in lockable toolbox
- » LiquidLocker™ baffle system fitted
- » 65mm 4T-rated solid galvanised axles with 15" Landcruiser wheels which provide high ground clearance and manoeuvrability with wheel nut indicators fitted
- » Recessed LED combination tail lights & license plate light
- » Large, 455mm lid opening with breather and filler cap
- » 10m retractable reel with anti-kink 25mm hose & 1" Nozzle
- » Fitted with a 4-digit mechanical flow meter for accurate fuel measurement
- » Cartridge filter fitted for pump protection and clean fuel delivery
- » 2" Lockable filling point
- » Puncture resistant 6 ply radial tyres, helping heavy load capability
- » Heavy duty jockey wheel and chequer plate mudguards
- » ROVER Vehicle Type Approval – Certified & Compliant
- » Hydraulic Override Braked (On-Road/Registrable) – On Farm (Unbraked) option available

SPECIFICATIONS

Tank Material	Polyethylene
Lid Diameter	455mm
Safety Baffles	Fitted
Capacity (brim full)	1000 Litres
Weight (Unbraked)	490kg
Weight (Braked)	500kg
Dimensions (Unbraked)	3600 x 1900 x 1240mm
Dimensions (Braked)	3600 x 1900 x 1450mm
Tank Warranty	25-Year
Frame Warranty	5-Year
Pump Warranty	2-Year