

DieselPatrol15™ 2400L

Duel Axle Refueling Trailer

SKU: DRXD2400L060V1 (UNBRAKED)

SKU: DRQD2400L060V1 (BRAKED)

TTi's DieselPatrol15™ Refueling Trailers provide safe and hassle-free refueling for your plant and equipment. Our diesel refueling trailers feature a robust galvanized chassis, moulded poly diesel tanks, high flow pumps, and hose reels, ultimately delivering effortless refueling of equipment.



- » Heavy-duty, fully-drainable, UV Stabilised poly tank with 25-year warranty
- » Built to high-level ADR requirements – manufactured from specially formulated diesel-grade polyethylene, complying with Australian Standards AS1940-2004 and AS2809.2-2008 for the safe transportation of flammable liquids and dangerous goods by road.
- » Strong heavy-duty Hot-dipped galvanised chassis with 50mm tow hitch
- » 60L/min 12v Piusi pump mounted in lockable toolbox
- » LiquidLocker™ baffle system fitted
- » 65mm 4T-rated solid galvanised axles with 15" Landcruiser wheels which provide high ground clearance and manoeuvrability with wheel nut indicators fitted
- » Recessed LED combination tail lights & license plate light
- » Large, 455mm lid opening with breather and filler cap
- » 10m retractable reel with anti-kink 25mm hose & 1" Nozzle
- » Fitted with a 4-digit mechanical flow meter for accurate fuel measurement
- » Cartridge filter fitted for pump protection and clean fuel delivery
- » 2" Lockable filling point
- » Puncture resistant 6 ply radial tyres, helping heavy load capability
- » Heavy duty jockey wheel and chequer plate mudguards
- » ROVER Vehicle Type Approval – Certified & Compliant
- » Hydraulic Override Braked (On-Road/Registrable) – On Farm (Unbraked) option available

SPECIFICATIONS

| | |
|-----------------------|----------------------|
| Tank Material | Polyethylene |
| Lid Diameter | 455mm |
| Safety Baffles | Fitted |
| Capacity (brim full) | 2400 Litres |
| Weight (Unbraked) | 860kg |
| Weight (Braked) | 870kg |
| Dimensions (Unbraked) | 5000 x 2150 x 2790mm |
| Dimensions (Braked) | 5000 x 2150 x 2790mm |
| Tank Warranty | 25-Year |
| Frame Warranty | 5-Year |
| Pump Warranty | 2-Year |